

SAFETY DATA SHEET

Report No.: CMC241022017M01

Name of sample: Lithium-ion Battery

Model: 803448

Type: 3.7V 1500mAh 5.55Wh

Client: Dong Guan Golden CEL Battery Co., Ltd.

Address: No.11, Yinhu Industrial park, JiaoYiTang Management Zone, TangXia, DongGuan, GuangDong, P.R. China

Written: Approved:

Reviewed: Dy lan Dou

Date of issue: 2025.01.01 Seal of CMC

CMC Testing International (Shenzhen) Co., Ltd.

The supplier identified below generated this SDS using the CMC SDS template. CMC did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. CMC makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS.

1-3F, Building 7, He'er Hongben Industrial Zone, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen, Guangdong, China 400-1668-320 info@cmczj-lab.com www.cmczj-lab.com 1 / 15



Safety Data Sheet

Section 1- Identification of the Substance/Preparation and of the Company/Undertaking			
(a) Product identifier			
Name of Sample	Lithium-ion Battery	Weight	24.6g
Name of Sample		Size (L×W×T)	(48.6×33.4×7.6)mm
Model	803448		
(b) Other means of identif	ication		
Synonyms:	None		
(c) Recommended use of	the chemical and restrictions on ι	use	
Recommended use:	LITHIUM ION BATTERIES		
Restriction on use:	striction on use: No information available.		
(d) Details of the supplier	of the product		
Manufacturer	Dong Guan Golden CEL Battery Co., Ltd.		
Manufacturer's Address	No.11, Yinhu Industrial park, JiaoYiTang Management Zone, TangXia, DongGuan, GuangDong, P.R. China		
Contact Person	Mr. Zhi		
E-mail	zhirongjian@celbattery.com		
Telephone:	+86-769-82195308-8016		
Fax:	+86-769-87982226		
(e) Emergency phone number	+86-769-82195308-8016		

Section 2- Hazards Identification

(a) Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) This product is an article which is a sealed battery and as such does not require an MSDS per the OSHA hazard communication standard unless ruptured. The hazards indicated are for a ruptured battery.

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 3
Skin corrosion/irritation	Category 1 Sub-category B
Serious eye damage/eye irritation	Category 1



Specific target organ toxicity (repeated exposure)	Category 1
Carcinogenicity	Category 2
Skin sensitization	Category 1

(b) GHS Label elements, including precautionary statements

Emergency Overview

Signal word: Danger Hazard Statements

Harmful if swallowed

Causes severe skin burns and eye damage

May cause an allergic skin reaction

Suspected of causing cancer

Causes damage to organs through prolonged or repeated exposure



This product is an article which contains a chemical substance. Safety information is given for exposure to the article as sold. Intended use of the product should not result in exposure to the chemical substance This is a battery. In case of rupture: the above hazards exist.

Appearance Gold	Physical State Solid Odor Odorless	
Precautionary Statements- Prevention	Obtain special instructions before use Do not handle until all safety precautions have been read and understo Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Do not breathe dust/fume/gas/mist/vapors/spray Do not eat, drink or smoke when using this product Contaminated work clothing should not be allowed out of the workplace Wear protective gloves	
Precautionary Statements- Response IF EXPOSED OR CONNECTED: Get medical advice/attention. Spet treatment (see supplemental first aid/instruction on this label). IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing Immediate call a POISON CENTER or doctor/physician. IF ON SKIN: Wash with plenty of soap and water. Take off contamine clothing and water before reuse, if skin irritation or rash occurs: get medical advice/attention if feel unwell. IF INHALATION: If breathing is difficult, remove victim to fresh air arkeep at rest in a position comfortable for breathing. If experiencing		,

1-3F, Building 7, He'er Hongben Industrial Zone, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen, Guangdong, China
400-1668-320 info@cmczj-lab.com www.cmczj-lab.com 3 / 15



	respiratory symptoms: Call a poison center or doctor/physician. IF SWALLOWED: Rinse mouth, do not induce vomiting, call a poison center or doctor/physician if feel unwell.
Precautionary Statements- Storage	Store locked up
Precautionary Statements- Disposal	Dispose of contents/container to an approved waste disposal plant
(c) Hazards not otherwise classified (HNOC)	Not applicable
(d) Unknown Toxicity	
(e) Other information	Very toxic to aquatic life with long lasting effects; Repeated or prolonged skin contact may cause allergic reactions with susceptible persons.
(f) Interactions with Other Chemicals	No information available.

Section 3- Composition/Information on Ingredients

Chemical Name	CAS Number	Weight-%	Trade Secret
Lithium Cobalt Oxide (LiCoO ₂)	12190-79-3	37.47	*
Graph <mark>ite</mark>	7782-42-5	15.35	*
Copper	7440-50-8	10.36	*
Aluminu <mark>m foil</mark>	7429-90-5	9.25	*
Polyprop <mark>ylene</mark>	9003-07-0	1.54	*
1,1-Difluoroethylene polymer	249 <mark>37-79-9</mark>	1.52	*
Polyethylene	9002-88-4	3.15	*
Styrene-Butadiene polymer	9003-55-8	0.86	*
Carboxymethy <mark>l cellulose</mark>	9000-11-7	0.74	*
Nickel	7440-02-0	1.34	*
Phosphate(1-), hexafluoro-, lithium	21324-40-3	17.49	*
Nylon	24937-16-4	0.93	*

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.



Section 4- First Aid Measures			
(a) Description of first aid measures			
General Advice	First aid is upon rupture of sealed battery.		
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Seek immediate medical attention/advice.		
Skin contact:	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Immediate medical attention is required. May cause an allergic skin reaction. Remove and isolate contaminated clothing and shoes.		
Inhalation:	Inhalation: Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Do not use mouth-to-mouth method, if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur. Get medical attention immediately if symptoms occur.		
Ingestion:	Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.		
Self-protection of the first aider:	Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8).		
(b) Most importan <mark>t sy</mark>	mptoms/effects, acute and delayed		
Most important symptoms and effects:	Itching. Coughing and/ or wheezing. Burning sensation.		
(c) Indication of a <mark>ny i</mark>	mmediate medical attention and special treatment needed		
Notes to Physician	Treat symptomatically. May cause sensitization of susceptible persons.		
Section 5- Fire Fighting I	Measures		
(a) Extinguishing media			
Suitable extinguishing media:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.		
Unsuitable extinguishing media:	CAUTION: Use of water spray when fighting fire may be inefficient.		
(b) Special hazards arising from the chemical			
The product causes burns of eyes, skin and mucous membranes. Thermal decomposition can lead to release of irritating gases and vapors. Product is or contains a sensitizer. May cause sensitization by skin contact.			
Hazardous Combustion Products	Carbon oxides.		

1-3F, Building 7, He'er Hongben Industrial Zone, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen, Guangdong, China
400-1668-320 info@cmczj-lab.com www.cmczj-lab.com 5 / 15



Evaluation Data	Sensitivity to Mechanical Impact:	No.
Explosion Data	Sensitivity to Static Discharge:	No.
(c) Special protective equipment and precautions for fire-fighters		

(c) Special protective equipment and precautions for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6- Accidental Release Measures

(a) Personal precautions, protective equipment and emergency procedures

Personal Precautions:	Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak.
Other Information:	Refer to protective measures listed in Sections 7 and 8.

(b) Environmental Precautions

Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.

(c) Methods and materials for containment and cleaning up

Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Pick up and transfer to properly labeled containers.

Section 7- Handling and Storage

(a) Precautions for safe handling

	Handle in accordance with good industrial hygiene and safety practice. Wear
	personal protective equipment. Avoid contact with skin, eyes or clothing. Ensure
	adequate ventilation. Do not eat, drink or smoke when using this product. Take off
	contaminated clothing and wash before reuse.

(b) Conditions for safe storage, including any incompatibilities

Storage:	Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Keep out of the reach of children.
Incompatible Products:	Acids. Bases. Oxidizing agent.

Section 8 - Exposure Controls/Personal Protection

(a) Control parameters

Exposure Guidelines	ACGIH TLV	OSHA PEL	NIOSH IDLH
Lithium Cobalt Oxide (LiCoO ₂) 12190-79-3	TWA: 0.02 mg/m³	-	-

1-3F, Building 7, He'er Hongben Industrial Zone, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen, Guangdong, China
400-1668-320 info@cmczj-lab.com www.cmczj-lab.com 6 / 15



Graphite 7782-42-5	TWA:1mg/m³ respirable fraction all forms except graphite fibers	TWA: 15 mg/m³ total dust synthetic TWA: 5 mg/m³ respirable fraction Synthetic (vacated) TWA: 2.5 mg/m³ respirable dust natural (vacated) TWA: 10 mg/m³ total dust synthetic (vacated) TWA: 5 mg/m³ respirable fraction synthetic TWA: 15 mppcf natural	IDLH: 1250 mg/m³ TWA: 2.5 mg/m³ respirable dust
Phosphate(1-), hexafluoro-, lithium 21324-40-3	TWA:2.5mg/m³ F	TWA:2.5mg/m³ F TWA:2.5mg/m³ dust (vacated)TWA:2.5mg/m³	
Copper 7440-50-8	TWA:0.2mg/m³ fume TWA:1mg/m³Cu dust and mist	TWA:0.1mg/m³fume TWA:1mg/m³dust and mist (vacated) TWA:0.1mg/m³Cu dust,fume,mist	IDLH:100mg/m³dust ,fume and mist TWA:1mg/m³dust and mist TWA:0.1mg/m³ fume
Aluminum foil 7429-90-5	TWA:1mg/m³ respirable fraction	TWA:15mg/m³ total dust TWA:5mg/m³respirable fraction (vacated) TWA:15mg/m³total dust (vacated) TWA:5mg/m³ respirable fraction(vacated) TWA:5mg/m³ AL Aluminum	TWA:10mg/m³ total dust TWA:5mg/m³ respirable dust
Nickel 7440-02-0	TWA:1.5mg/m³	TWA:1mg/m³ (vacated) TWA:1 mg/m³	IDLH:10mg/m³ TWA:0.015mg/m³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value

OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines	Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters		
(b) Appropriate en <mark>gineering</mark>	g controls		
	Showers		
Engineering Measur <mark>es</mark>	Eyewash stations		
	Ventilation systems		
(c) Individual protection measures, such as personal protective equipment.			
Eye/Face Protection:	None required for consumer use. If there is a Hazard of contact:. Tight sealing safety goggles. Face protection shield.		
Skin and Body Protec <mark>tion:</mark>	None required for consumer use. If there is a Hazard of contact:. Wear protective gloves and protective clothing.		
Respiratory Protection No protective equipment is needed under normal use conditions. If exp limits are exceeded or irritation is experienced, ventilation and evacuation be required.			



Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. For environmental protection, remove and wash all contaminated protective equipment before re-use. No information available.

Section 9- Physical and Chemical Properties					
(a) Physical State					
Physical state:	Solid				
Appearance:	Gold Cu	boid	boid Odor:		Odorless
Color:	Gold		Odor Threshold:		No information available
(b) Chemical Properties					
Property		Values		Remarks/ Method	
pH		No data available		None kr	nown
Melting point/freezing point	t	No data available		None kr	nown
Initial Boiling Point And Boiling Range	iling	No data available		None known	
Flash Point		No data available		None known	
Evaporation Rate		No data available		None known	
Flammability (Solid, Gas)		No data available		None known	
Upper/Lower Flammability Or Explosive Limits		No data available			
Vapor Pressure	por Pressure			None kr	nown
Vapor Density		No data available		None known	
Relative Density		No data available		None known	
Solubility(les)		Insoluble in water		None known	
Partition Coefficient: N-Octanol/Water		No data available		None known	
Auto-Ignition Temperature		No data available		None known	
Decomposition Temperature		No data available		None known	
Kinematic viscosity		No data available		None known	
Dynamic viscosity		No data available		None known	
Explosive properties		No data available			
Oxidizing Properties		No data available			
(c) Other Information					
Softening Point		No data available			



VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	No data available No data available No data available

Section 10 – Stability and Reactivity		
(a) Reactivity	No data available.	
(b) Chemical stability	Stable under recommended storage conditions.	
(c) Possibility of hazardous reactions	None under normal processing.	
(d) Hazardous polymerization	Hazardous polymerization does not occur.	
(e) Conditions to avoid	None known based on information supplied.	
(f) Hazardous decomposition products	Carbon oxides.	

Section 11 – Toxicological Information					
(a) Information on t	he lil	kely routes of exposure			
Product Information		Product does not present an ac In case of rupture:	Product does not present an acute toxicity hazard based on known or supplied information. In case of rupture:		
Inhalation		Specific test data for the sub of respiratory tract.	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract.		
Eye Contact		Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to eyes. May cause redness, itching, and pain. May cause temporary eye irritation.			
Skin Contact		Specific test data for the substance or mixture is not available. Corrosive. (based on components). Causes burns. May be absorbed through the skin in harmful amounts. Harmful in contact with skin.			
Ingestion		Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be harmful if swallowed.			
Component Informa	Component Information				
Chemical Name		Oral LD50	Dermal LD50	Inhalation LC50	
Graphite 7782-42-5		> 10000 mg/kg (Rat)	-	-	
Nickel 7440-02-0		>9000 mg/kg (Rat)	-	-	
(b) Information on toxicological effects					
Symptoms Erythema (skin redness). May cause redness and tearing of the eyes. Itching. Rashes. Hives.			of the eyes. Itching.		

1-3F, Building 7, He'er Hongben Ind	ustrial Zone, Dawangshan Community, Sha	ajing Street, Bao'an District, Shenzhen, G	Buangdong, China
400-1668-320	info@cmczj-lab.com	www.cmczj-lab.com	9 / 15



(c) Delayed and immedia	ate effects as well as chronic effects from short and long-term exposure
	May cause consitization of susceptible persons. May cause consitization by skin

Sensitization: May cause sensitization of susceptible persons. May cause sensitization by skin contact.

Mutagenic Effects: No information available.

Carcinogenicity:

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Lithium Cobalt Oxide				
(LiCoO ₂)	A3	Group 2B		X
12190-79-3				
Nickel		Group 2B	Decembly Anticipated	V
7440-02-0		Group 2B	Reasonably Anticipated	^

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive Toxicity	No information available.	
STOT - single expos <mark>ure</mark>	No information available.	
STOT - repeated exposure	Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).	
Chronic Toxicity	Contains a known or suspected carcinogen. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse liver effects.	
Target Organ Effects	Respiratory system. Eyes. Skin. Gastrointestinal tract (GI). Central Vascular System (CVS).Kidney. Liver. Lungs. Heart.	
Aspiration Hazard	No information available.	

(d) Numerical measures of toxicity Product Information

The following values are calculated based on	ATEmix (oral):
chapter 3.1 of the G <mark>HS document</mark>	ATEmix (dermal):



Section 12-Ecological Information

(a) Ecotoxicity

Very toxic to aquatic life with long lasting effects.

Section 13 – Disposal Considerations

(a) Waste treatment methods

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Copper	96h EC50: 0.031 - 0.054	96h LC50: 0.0068 - 0.0156		48h EC50: = 0.03
7440-50-8	mg/L (Pseudokirchneriella	mg/L (Pimephales romelas)		mg/L
	subcapitata) 72h EC50:	96h LC50: = 0.112 mg/L		
	0.0426 - 0.0535 mg/L	(Poecilia reticulata) 96h		
	(Pseudokirchneriella	LC50: = 0.3 mg/L (Cyprinus		
	subcapitata)	carpio) 96h LC50: =		
		0.8mg/L (Cyprinus carpio)		
		96h LC50: = 1.25 mg/L		
		(Lepomis macrochirus) 96h		
		LC50: =0.052 mg/L		
		(Oncorhynchus mykiss) 96h		
		LC50: = 0.2mg/L		
/	(Pimephales promelas)			
		96h LC50: < 0.3 mg/L		
		(Pimephales promelas)		
Nickel	72h EC50: = 0.18 mg/L			48h EC50: > 100
7440-02-0	(Pseudokirchneriella	, , , ,		mg/L 48h EC50:
	subcapitata) 96h EC50:	ubcapitata) 96h EC50: LC50: = 1.3 mg/L (Cyprinus		= 1 mg/L
	0.174 - 0.311 mg/L	174 - 0.311 mg/L carpio) 96h LC50: = 10.4		
	(Pseudokirchneriella	Pseudokirchneriella mg/L (Cyprinus carpio)		
	subcapitata)			
(b) Persistence and Degradability	No information available.			
(c) Bioaccumulation	No information availal	No information available		
(d) Other adverse effects	No information available.			

· ,	
Disposal methods:	This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR
	261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.
Contaminated	Disposal should be in accordance with applicable regional, national and local laws

Packaging:	and regulations.			
Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Nickel 7440-02-0	(hazardous constituent -	Included in waste		

1-3F, Building 7, He'er Hongben Industrial Zone, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen, Guangdong, China
400-1668-320 info@cmczj-lab.com www.cmczj-lab.com 11 / 15



California Hazardous Waste Codes 141

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name California Hazardous Waste	
Lithium Cobalt Oxide (LiCoO ₂) 12190-79-3	Toxic
Copper 7440-50-8	Toxic
Aluminum foil 7429-90-5	Ignitable powder
Nickel	Toxic powder
7440-02-0	Ignitable powder

Section 14 – Transport	Section 14 – Transport Information			
UN number	UN3480 Lithium ion batteries (including lithium ion polymer batteries) (limited to a maximum of 30% SoC).			
Hazard Class:	Class 9	Class 9 Packing grade: /		
UN number	UN3481 Lithium ion batteries packed with equipment (including lithium ion polymer batteries) or; Lithium ion batteries contained in equipments (including lithium ion polymer batteries).			
Hazard Class:	1	Packing grade:	1	
	ch a user needs to be awar thin or outside their premise		rith, in connection with transport	
ICAO / IATA:	(ICAO), TI or International Instructions (PI) 965 Sections	Can be shipped by air in accordance with International Civil Aviation Organization (ICAO), TI or International Air Transport Association (IATA), DGR Packing Instructions (PI) 965 Section IB, PI 966 Section II and PI 967 Section II appropriate of IATA DGR 66th (2025 Edition) for transportation.		
IMDG CODE:	The batteries are not rest to special provision 188.	tri <mark>cted to IM</mark> DG Code 2022	2 Edition (Amdt 41-22) according	
UN number	Lithium ion batteries (including lithium ion polymer batteries). UN3481 Lithium ion batteries packed with equipment (including lithium ion polymer batteries) or; Lithium ion batteries contained in equipments (including lithium ion polymer batteries).			
Hazard Class:	/ Packing grade: /			
EmS No.	F-A S-I			

1-3F, Building 7, He'er Hongben Industrial Zone, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen, Guangdong, China
400-1668-320 info@cmczj-lab.com www.cmczj-lab.com 12 / 15



ADR/ ADN:

The batteries are not subject to the provisions of United Nations Economic Commission for Europe (UNECE) ADR/ADN if they meet the requirements of special provision 188 of Chapter 3.3. Applicable as from 1 January 2023.

In addition, to be permitted in transport each lithium cell and battery types must have passed the applicable tests set out in Subsection 38.3 of the UN Manual of Tests and Criteria. The batteries should be well protected against short circuits.

Section 15 - Regulatory Information

(a) International Inventories

TSCA:	Complies.
DSL:	All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

(b) US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 – Threshold Values %
Lithium Cobalt Oxide (LiCoO ₂)	12190-79-3	37.47	0.1
Copper	7440-50-8	10.36	1.0
Aluminum foil	7429-90-5	9.25	1.0
Nickel	7440-02-0	1.34	0.1

SARA 311/312 Hazard Categories

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Copper 7440-50-8		X	Х	
Nickel 7440-02-0		x	×	

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

1-3F, Building 7, He'er Hongben Industrial Zone, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen, Guangdong, China
400-1668-320 info@cmczj-lab.com www.cmczj-lab.com 13 / 15



Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Copper	5000 lb		RQ 5000 lb final RQ
7440-50-8	3000 lb		RQ 2270 kg final RQ
Aluminum foil			
7429-90-5			
Nickel	400 lb		RQ 100 lb final RQ
7440-02-0	100 lb		RQ 45.4 kg final RQ

(c) US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Propos <mark>itio</mark> n 6 <mark>5</mark>
Nickel - 7440-02-0	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Lithium Cobalt Oxide (LiCoO ₂) 12190-79-3	X		Х	X	Х
Graphite 7782-42-5	Х	x	Х		
Copper 7440-50-8	Х	x	Х	х	х
Aluminum foil 7429-90-5		x		X	
Nickel 7440-02-0	X	x	X	X	X

(d) International Regulations

Mexico

National occupational exposure limits

Compon <mark>ent</mark>	Carcin <mark>ogen Status</mark>	Exposure Limits
Graphit <mark>e</mark> 7782-42- <mark>5</mark>		Mexico: TWA= 2 mg/m3
Copper 7440-50- <mark>8</mark>		Mexico: TWA= 1 mg/m3 Mexico: TWA= 0.2 mg/m3 Mexico: STEL= 2 mg/m3
Aluminum <mark>foil</mark> 7429-90-5		Mexico: TWA 10 mg/m3
Nickel 7440-02-0		Mexico: TWA= 1 mg/m3

Mexico - Occupational Exposure Limits - Carcinogens



Canada

WHMIS Hazard Class


Non-controlled

Section 16 - Additional Information

NFPA	Health Hazards	1	Flammability	0	Instability	0	Physical and Chemical Hazards	-
нміѕ	Health Hazards	0	Flammability	0	Physical Hazard	0	Personal Protection	x

Revision Note: No information available

Sample photo:



Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

******End of report*****

Testing laboratory: CMC Testing International (Shenzhen) Co., Ltd.

Address: 1-3F, Building 7, He'er Hongben Industrial Zone, Dawangshan Community, Shajing Street, Bao'an District, Shenzhen, Guangdong, China